COSHH ASSESSMENT MORTAR

Product Name(s):	М	Mortar				COSHH Assess.	No.:	4	23
Description of Substance:	f Si	te prep	ared morta	ar		Assesse	d By:		
Workplace Exposure Lim	oits:	alcium <i>i</i>	Aluminium	10mg/m ³		Date:			
Task/Activity:		Trowel applied mixture of Portland cement, sand and chemical additives such as retardants.					such as		
Suppliers Nan	ne						Telephone/ Fax No's:		
& Address:						MSDS Attached	Yes / No		lo
SUBSTANCE PROPERTIES									
							*	13	L.U
Flammable/ Highly Flammable	Oxidiser		Explosive	Harmful	Toxic/ Very Toxic	Irritant	1	erous to the onment	Corrosive
No	No		No	Yes	No	Yes	Y	'es	No

ROUTE OF EXPOSURE						
Skin	х	Eyes	x	Inhalation		
Ingestion		Cuts/ Abrasions	Х	Injection		

PERSONS AT RISK						
Users of the product	X	Members of Public		Visitors		
Other Workers		Young Persons				

PPE REQUIREMENTS							
						Other:	Other:
Yes	Yes	No	No	Yes	No	Yes / No	Yes / No

ADDITIONAL CONTROL MEASURES					
General Precautions	Control Measures				
Ensure that the above specified PPE is worn and that all staff are informed of the risks; control measures and precautions required when working with the substance.	Ensure that adequate supervision is provided at all times.				

COSHH ASSESSMENT MORTAR

First Aid/Hygiene Arrangements	Fire Precautions
 Wash skin thoroughly with soap and clean water If contact is made with the eye, immediately flood the eye with plenty of clean water for at least 10 minutes and seek immediate medical attention. If inhalation or ingestion occurs, seek immediate medical attention. Wash out the mouth with clean water where appropriate. 	➤

LEV Requirements	Monitoring Requirements			
Ensure that the work area is well ventilated at all times.	 Consider additional monitoring if this product is to be used within a confined space. Provide additional monitoring where young or inexperienced workers are carrying out the works. 			

Transport Arrangements	Storage Requirements		
> No special requirements for small quantities	 Store in a dry, well ventilated and secure store. Always store upright with the lids firmly secured. Protect from extremes of temperature. 		

S	pillage Procedures	Disposal Requirements		
A	Spillages should be cleaned up with a brush and shovel.	Dispose of waste as normal builders waste.		

Comments

This is only a preliminary assessment based on generic information for similar products.

This assessment must be reviewed and amended by a competent person prior to its contents being used. This is to ensure that consideration is given to site specific circumstances or differences which may affect the original assessment. It is the employers responsibility to ensure that a suitable and sufficient assessment of the risks is undertaken when using any material which may be hazardous to health.

An up to date Material Safety Data Sheet (MSDS) should be obtained from the supplier and reviewed alongside this assessment to ensure that the control measures are suitable and remain valid.