COSHH ASSESSMENT READY MIXED CERAMIC TILE GROUT AND ADHESIVE

Product Name(s):	Ready	Ready mixed ceramic tile grout and adhesive			COSHH Assess. I	No.:		29
Description of Substance:	Cemen	Cementitious tile adhesive				d By:		
Workplace Exposure Limit		Nuisance Dust 8 Hour TWA 10 Mg/m³ Inhalable 4 Mg/m³ Respirable						
Task/Activity:	Fixing a	Fixing and grouting of ceramic tiles.						
Suppliers Name	е					ie/		
& Address:					MSDS Attached	:	Yes / N	No
		SI	UBSTANCE P	ROPERTIES				
						*		L.Un
Flammable/ Highly Flammable	Oxidiser	Explosive	Harmful	Toxic/ Very Toxic	Irritant	t	erous to the onment	Corrosive
No	No	No	No	No	Yes	1	No	No

ROUTE OF EXPOSURE						
Skin	X Eyes Inhalation X					
Ingestion		Cuts/ Abrasions		Injection		

PERSONS AT RISK					
Users of the product	X	Members of Public		Visitors	
Other		Young			
Workers		Persons			

PPE REQUIREMENTS							
						Other:	Other:
Yes	No	Yes	No	Yes	No	Yes/No	Yes/No

ADDITIONAL CONTROL MEASURES					
General Precautions	Control Measures				
Ensure that the above specified PPE is worn and that all staff are informed of the risks; control measures and precautions required when working with the substance.	Ensure that adequate supervision is provided at all times.				

COSHH ASSESSMENT READY MIXED CERAMIC TILE GROUT AND ADHESIVE

First Aid/Hygiene Arrangements	Fire Precautions			
 Wash skin thoroughly with soap and clean water If contact is made with the eye, immediately flood the eye with plenty of clean water for at least 10 minutes and seek immediate medical attention. If inhalation or ingestion occurs, seek immediate medical attention. Wash out the mouth with clean water where appropriate. 	No smoking to be permitted in the vicinity of the works.			

LEV Requirements	Monitoring Requirements		
Ensure that the work area is well ventilated at all times.	 Consider additional monitoring if this product is to be used within a confined space. Provide additional monitoring where young or inexperienced workers are carrying out the works. 		

Transport Arrangements		Storage Requirements		
A	No special requirements for small quantities	AAA	Store in a dry, well ventilated and secure store. Always store upright with the lids firmly secured. Protect from extremes of temperature.	

Spillage Procedures	Disposal Requirements		
	 Dispose of waste containers etc as normal builders waste 		

Comments

This is only a preliminary assessment based on generic information for similar products.

This assessment must be reviewed and amended by a competent person prior to its contents being used. This is to ensure that consideration is given to site specific circumstances or differences which may affect the original assessment. It is the employers responsibility to ensure that a suitable and sufficient assessment of the risks is undertaken when using any material which may be hazardous to health.

An up to date Material Safety Data Sheet (MSDS) should be obtained from the supplier and reviewed alongside this assessment to ensure that the control measures are suitable and remain valid.