## COSHH ASSESSMENT ROOF FELT ADHESIVE

Product Name(s):	Roof Felt Adhesive			COSHH Assess. N	lo.:	4	31	
Description of Substance:	Bitumen ba	ased adhesiv	е		Assessed	l By:		
Workplace Exposure Limits:	White Spir	it 100 ppm (8	Hr TWA)		Date:			
Task/Activity:	Brush app	Brush applied roofing adhesive.						
Suppliers Name					Telephon Fax No's:			
& Address:					MSDS Attached:		Yes / N	10
	-	SUB	STANCE PRO	PERTIES	-			
					*	*		VA.
Flammable/ Highly Flammable	Oxidiser	Explosive	Harmful	Toxic/ Very Toxic	Irritant	t	erous to he onment	Corrosive
Yes	No	No	No	Yes	Yes	Y	'es	No

ROUTE OF EXPOSURE					
Skin	Х	Eyes	X	Inhalation	х
Ingestion	Х	Cuts/ Abrasions		Injection	

PERSONS AT RISK					
Users of the product	X	Members of Public		Visitors	
Other		Young			
Workers		Persons			

			PPE REQUIRE	MENTS			
<b>33</b>						Other:	Other:
Yes	Yes	Yes	No	Yes	No	Yes / No	Yes / No

ADDITIONAL CONTROL MEASURES				
General Precautions	Control Measures			
Ensure that the above specified PPE is worn and that all staff are informed of the risks; control measures and precautions required when working with the substance.	Ensure that adequate supervision is provided at all times.			

## COSHH ASSESSMENT ROOF FELT ADHESIVE

First Aid/Hygiene Arrangements	Fire Precautions			
<ul> <li>Wash skin thoroughly with soap and clean water</li> <li>If contact is made with the eye, immediately flood the eye with plenty of clean water for at least 10 minutes and seek immediate medical attention.</li> <li>If inhalation or ingestion occurs, seek immediate medical attention.</li> <li>Wash out the mouth with clean water where appropriate.</li> </ul>	<ul> <li>No smoking to be permitted in the vicinity of the works.</li> <li>No hot works to be allowed in the vicinity of the works.</li> <li>Use CO2 or dry powder extinguisher</li> </ul>			

LEV Requirements	Monitoring Requirements			
Ensure that the work area is well ventilated at all times.	<ul> <li>Consider additional monitoring if this product is to be used within a confined space.</li> <li>Provide additional monitoring where young or inexperienced workers are carrying out the works.</li> </ul>			

Transport Arrangements	Storage Requirements			
No special requirements for small quantities	<ul> <li>Store in a dry, well ventilated and secure store.</li> <li>Always store upright with the lids firmly secured.</li> <li>Protect from extremes of temperature.</li> </ul>			

Sp	Spillage Procedures		sposal Requirements
<b>A</b>	Spillages should be contained and cleaned up using a proprietary spill kit/absorbent pads. These should then be placed into a suitable container for disposal.	A	Dispose of waste containers etc as normal builders waste via a licensed waste contractor.

## Comments

This is only a preliminary assessment based on generic information for similar products.

This assessment must be reviewed and amended by a competent person prior to its contents being used. This is to ensure that consideration is given to site specific circumstances or differences which may affect the original assessment. It is the employers responsibility to ensure that a suitable and sufficient assessment of the risks is undertaken when using any material which may be hazardous to health.

An up to date Material Safety Data Sheet (MSDS) should be obtained from the supplier and reviewed alongside this assessment to ensure that the control measures are suitable and remain valid.